



5043 Farlin Ave.  
 St. Louis, MO 63115  
[www.associatedequip.com](http://www.associatedequip.com)

## MODEL IBC6008

- *12V 60 Amp 270 Amp Boost wheel charger*
- *Adjustable Charging Voltage and Amperage*
- *Adjustable Voltage Re-flash Power Mode*
- *Partial Charge Mode*
- *Patented Battery Diagnostics*
- *Designed to Vehicle Manufacturer and Battery Manufacturer Requirements*

### Specifications:

<b>Model Number</b>	<b>IBC6008</b>
<b>Battery Types</b>	<b>12 Volt Standard Flooded, AGM, Gel, EFB, Lithium and Deep Cycle batteries</b>
<b>Display</b>	<b>Four-line backlit digital display</b>
<b>DC Leads</b>	<b>6 ½' 4 AWG</b>
<b>Clamp Rating</b>	<b>400A</b>
<b>AC Cord</b>	<b>6' 16-3</b>
<b>Power Requirements and Consumption</b>	<b>12A 120VAC 60 Hz</b>
<b>Charger Output</b>	<b>13.8V-60A. Crank 7.2V-260A</b>
<b>Power Supply Output</b>	<b>13.8V – 60A. Can output 70A at lower voltage for &lt;10 min.</b>
<b>Industry Approval</b>	<b>UL/CUL</b>
<b>Limited Warranty</b>	<b>Two Years Parts/Labor-Three Years Transformer/Rectifier</b>
<b>Country of Origin</b>	<b>MADE IN USA of US and Global Components</b>
<b>UPC</b>	<b>099684006972</b>
<b>HTC</b>	<b>8203.10.9000</b>
<b>Shipping Dimensions</b>	<b>17.25"x16.5"x26.5"</b>
<b>Weight</b>	<b>47 LBS</b>



5043 Farlin Ave.  
St. Louis, MO 63115  
[www.associatedequip.com](http://www.associatedequip.com)

## MODEL IBC6008MSK

- *12V 60 Amp 270 Amp Boost wheel charger*
- *Adjustable Charging Voltage and Amperage*
- *Adjustable Voltage Re-flash Power Mode*
- *Partial Charge Mode and Patented Battery Diagnostics*
- *Designed to Vehicle Manufacturer and Battery Manufacturer Requirements*
- *20A Memory Saver Port and OBDII Cable*
- *Polarity Indicated and Polarity Protected with Audible Alarm*

### Specifications:

<b>Model Number</b>	<b>IBC6008MSK</b>
<b>Battery Types</b>	<b>12 Volt Standard Flooded, AGM, Gel, EFB, Lithium and Deep Cycle batteries</b>
<b>Display</b>	<b>Four-line backlit digital display</b>
<b>DC Leads</b>	<b>6 ½' 4 AWG</b>
<b>Clamp Rating</b>	<b>400A</b>
<b>AC Cord</b>	<b>6' 16-3</b>
<b>Power Requirements and Consumption</b>	<b>12A 120VAC 60 Hz</b>
<b>Charger Output</b>	<b>13.8V-60A. Crank 7.2V-260A</b>
<b>Power Supply Output</b>	<b>13.8V – 60A. Can output 70A at lower voltage for &lt;10 min.</b>
<b>Memory Saver Port</b>	<b>20A</b>
<b>Memory Saver Cord</b>	<b>MS6209-12 OBDII</b>
<b>Industry Approval</b>	<b>UL/CUL</b>
<b>Limited Warranty</b>	<b>Two Years Parts/Labor-Three Years Transformer/Rectifier</b>
<b>Country of Origin</b>	<b>MADE IN USA of US and Global Components</b>
<b>UPC</b>	<b>099684006989</b>
<b>HTC</b>	<b>8203.10.9000</b>
<b>Shipping Dimensions</b>	<b>17.25"x16.5"x26.5"</b>
<b>Weight</b>	<b>49 LBS</b>