

Tie Rod End Remover

10301 / 10302 / 10304 / 10306 / 10310

**TIGER
TOOL**

Have What It Takes

Safety Warning

Read all instructions and safety warnings prior to operation. Failure to do so could result in equipment damage, personal injury or even death.

- **Stay Alert!** Watch what you are doing and use common sense when operating this tool.
- Inspect product for damage prior to using; do not use if product is in unsafe condition.
- Do not operate tool while under the influence of drugs, alcohol or medication.
- Always use safety equipment to prevent injuries. Approved face and eye protection must always be worn by the operator, as well as others in the work area.
- Do not overreach. Keep proper footing and balance at all times.
- Dress properly. Do not wear loose clothing or jewelry. Keep your hair, clothing and gloves away from moving parts.
- Keep hands clear of all pressurized hydraulic components.
- Always ensure hoses are free from sharp bends and kinks.
- Keep your work area clean and well lit.

Operating Instructions

- 1 Remove the cotter pin and castle nut.
- 2 Select the corresponding sized Tie Rod End Remover.
- 3 Make sure tie rod end threads are clean and free of damage.
- 4 Thread on the tool until it bottoms out, then back it off one complete turn.
- 5 Strike the top of the tool with a hammer, tie rod will "pop" loose.
- 6 Remove the tool.

Here at Tiger Tool, your satisfaction is our number one priority. Should you have any questions about this or any of our products, please call us at 1.800.661.4661.



View demonstration videos and a complete product list at tigertool.com

Technical Support
1.800.661.4661