

PRODUCT DATA SHEET

VT40-HT HIGH TACK SERIES AUTO WRAP

General Product Description:

The VT40-HT-series Auto Wrap is a heavy duty 4 mil 3-layer CoEx film designed to provide surface and interior protection for a variety of outdoor automotive salvage and towing applications. Special polyethylene blend contains 25% metallocene to provide high resistance against puncture and tear. A UV additive offers outdoor protection for up to 60-days. Water based acrylic adhesive system provides instant tack even in demanding outdoor conditions and is safe to use.

Product Properties:

Film:		
Material		3-layer coex LDPE/LLDPE blend wt >25% metallocene + 3% UVI
Color		Clear
Film Gauge:		
ASTM D-1000		4.0 mil
Puncture Resistance:		
Dart D1709		325 g
Tensile Strength:		
D882 (MD)		6500 PSI
Tear Strength (Elmendorf):		
DASTM 1922 (MD)		1250 g
Elongation (at break):		
D882 (MD)		500 %
Adhesive Type:		
Type		Acrylic Copolymer
Base		Water
Adhesion to Steel:		
PSTC-1		16 +/- 2 oz/in

Notice to Buyers:

Except as otherwise provided herein, the quality shall be in accordance with the seller's specifications. Final determination of the suitability of the use contemplated by the buyer is the SOLE RESPONSIBILITY OF THE BUYER, and the seller shall have no responsibility in connection with such suitability.