



# V-Series™ Lightheads

## Combination Lighting

Featuring Whelen's innovative optic technology, V-Series Super-LED® lightheads are versatile and efficient. Utilizing multiple planes of light in one lighthead, models are available in a variety of sizes for use in numerous applications. Hard-coated lenses minimize environmental damage from sand, sun, salt, and road chemicals.



SAE 845 Class 1, 180° warning




White steady-burn flood/alley



White ground illumination



 WARNING: These products may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit [whelen.com/regulatory](http://whelen.com/regulatory).

# ION™ V-Series™



## FEATURES

- Combination models have 3-in-1 180° wide-angle warning, illumination, and puddle light
- Single color models have combination 180° and TIR directional warning
- Available in surface or universal mount
- Surface mount models include Black flange
- Available in Amber, Blue, Red, and White
- Universal mount includes combination permanent/pedestal, clip, edge mounts, double-sided tape, with a Black housing
- Warning segment has 25 Scan-Lock™ flash patterns
- Six inch pigtail with sync wire allows up to eight lightheads to be synchronized together for the warning segment of the lighthead
- SideKick™ and Mirror-Beam™ models include driver and passenger side housings
- Go undercover with SAE Class 1 Certified Smoked lenses
- Combination model: Amp Draw @ 12 VDC, Warning: 0.765/A, Flood: 0.31/A, Puddle: 0.12/A
- Single color warning model: Amp draw @ 12 VDC, Warning: 1.147/A
- Size, Universal mount: 1.02" (26mm) H x 2.21" (56mm) D x 4.09" (104mm) L
- Size, Surface mount: 1.69" (43mm) H x 1.98" (50mm) D x 5.91" (150mm) L

## Warning Certified To:

- SAE J595
- SAE J845

**⚠ WARNING:** These products may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit [whelen.com/regulatory](http://whelen.com/regulatory).

## MODELS

Model	Optics	Lens	Mount	Housing/Vehicle	
IONV1*	Single Color	Clear	Universal	Black Housing	
IONV1*W				White Housing	
XONV1*		Smoked		Black Housing	
IONV3*	3-in-1 Combination	Clear		Black Housing	
IONV3*W				White Housing	
XIONV3*		Smoked		Black Housing	
IONSV1*	Single Color	Clear	Surface	Black Housing	
IONSV1*W				White Housing	
IONSV1*C		Chrome Housing			
XIONSV1*		Smoked			Black Housing
IONSV3*	3-in-1 Combination	Clear			Black Housing
IONSV3*W				White Housing	
IONSV3*C		Chrome Housing			
XONSV3*		Smoked		Black Housing	
SK01V3**		Clear	SideKick	Ford Police Interceptor Sedan, 2013-2018	
XK01V3**		Smoked	Fender Mount		
VMCT15**	3-in-1 Combination	Clear	Mirror-Beam Mirror Mount	Chevy Tahoe and Suburban 1500, 2015-2018	
VXCT15**		Smoked			
VMDC11**		Clear		Dodge Charger, 2011-2018	
VXDC11**		Smoked			
VMFF17**		Clear	Mirror-Beam Mirror Mount	NEW Ford Fusion, 2015-2018	
VXFF17**		Smoked			
VMFT11**		Clear		Ford Police Interceptor Sedan, 2013-2018	
VXFT11**		Smoked			
VMFX11**		Clear		Ford Police Interceptor Utility, 2013-2018	
VXFX11**		Smoked			

Replace \* symbol in model number with letter indicating color desired:  
A=Amber, B=Blue, R=Red, C=White



## OPTIONS

IONK1B	For IONV Universal Mount Lighthead Only	Swivel Mount Bracket	Black
IONGROM		Grommet Mount Kit	
IONPEDB		Pedestal Mount Kit	
IONBKT1		Universal License Plate Bracket for 2 ION lightheads, horizontal mount, not for use with surface mount ION's	
IONBKT2		Rear Hatch Mounting Brackets (pair) for 2013-2017 Ford Police Interceptor Utility, for 6 ION's purch. sep.	
IONBKT4		Rear hatch brackets (pair), 2013-2017 Ford Police Interceptor Utility, for two ION's purchased separately	
IONBKT5		Universal Mount, reversed, allows access to mounting screws without removing the light	
IONBKT6	Rear hatch brackets (pair), 2015-2018 Chevy Tahoe, requires two ION's lightheads purchased separately		
IONBKT7	Grille mount brackets (pair) for 2015-2018 Chevy Tahoe, requires four ION's lightheads purchased separately		



# LINV2™ & LINSV2™ V-SERIES™



LINV2C



LINSV2B

## MODELS

Model	Mount	Lens	Housing
LINV2*	Surface Mount	Clear	Black
LINV2*X		Smoked	
LINSV2*	Under Surface Mount	Clear	
LINSV2*X		Smoked	

Replace \* symbol in model number with letter indicating color desired:  
A=Amber, B=Blue, R=Red, C=White



## OPTIONS

LINV2 Lighthouse Only		
RFLANGEC	Flange Mounting Kit	Chrome
L6BKT3	46° Push Bumper Bracket, each	Black
RBKT1	“L” Mounting Bracket for 1 Lighthouse	Aluminum
RBKT2	“L” Mounting Bracket for 2 Lighthouses	
RBKT4	Swivel mounting bracket	Black
RBKT6	License Plate Bracket for 2 Lighthouses, Horizontal Mount	Black
RBKT7	License Plate Bracket for 2 Lighthouses, Vertical Mount	
RBKT10	Trunk Mount Bracket for Dodge Charger, pair	
RBKT16	Trunk Mount Bracket for 2013-2018 Ford Police Interceptor Sedan, Pair	
LINV2 Lighthouse Only - Above or Below the Rear Taillight Mounting Bracket, Pair		
RBKT12	Above Bracket for Ford F-250/350/450/550, 2013-2016	Black
RBKT14	Above Bracket for Chevy Silverado 1500/ GMC 1500, 2014-2018	
RBKT17	Above Bracket for Dodge Ram, 2014-2018	
RBKT18	Above Bracket for Ford F-150, 2015-2018	
RBKT19	Below Bracket for Ford F-150, 2015-2018	
RBKT19	Below Bracket for Ford F-150, 2015-2018	
LINSV2 Lighthouse Only - Under-the-Side View Mirror Mount, Pair		
LSVBKT13	Chevy Silverado 1500/2500, 2014-2018	Black
LSVBKT34	Ford Police Interceptor Utility 2013-2018	
LSVBKT35	Dodge Charger, 2011-2018	
LSVBKT38	Ford Police Interceptor Sedan 2013-2018	
LSVBKT42	Dodge Ram 1500, 2011-2018	
LSVBKT44	Dodge Durango, 2013-2018	
LSVBKT47	Ford F-150, 2015-2018	
LSVBKT45	Chevy Tahoe and Suburban, 2015-2018	



## FEATURES

- Models have 2-in-1 combination warning and puddle light
- LINSV2 lighthouse with right angle bracket mounts beneath a side view mirror, push bumper, or under any flat mounting surface. Includes glamour cap
- LINV2 lighthouses include surface mount Black flange
- Warning segment has 25 Scan-Lock™ flash patterns
- Six inch pigtail with sync wire allows up to eight lighthouses to be synchronized together for the warning segment of the lighthouse
- Go undercover with SAE Class 1 Certified Smoked lenses
- Amp Draw @ 12 VDC, Warning: 0.75/A, Puddle: 0.12/A
- LINV2 Size: 1.576" (40mm) H x 1.65" (42mm) D x 3.876" (98mm) L
- LINSV2 Size: 1.1" (28mm) H x 2.80" (71mm) D x 2.89" (73mm) L

## Warning Certified To:

- SAE J595
- SAE J845 Selective Coverage (Amber)

**WARNING:** These products may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit [whelen.com/regulatory](http://whelen.com/regulatory).



# 500 V-Series™



## FEATURES

- Combination models have 3-in-1 180° wide-angle warning, illumination, and puddle light
- Single color models have combination 180° and TIR directional warning
- Warning segment has 25 Scan-Lock™ flash patterns
- Six inch pigtail with sync wire allows up to eight lighthead to be synchronized together for the warning segment of the lighthead
- Combination model: Amp Draw @ 12 VDC, Warning: 0.12/A, Flood: 1.0/A, Puddle: 0.5/A
- Single color warning model: Amp Draw @ 12 VDC, Warning: 1.5/P, 0.6/A
- Size: 2.13" (54mm) H x 1.64" (42mm) D x 5.39" (137mm) L

## Warning Certified To:

- SAE J845
- CAC Title XIII (Blue)



5V1R



5V3A

## MODELS

5V1*	Single Color Warning
5V3*	3-in-1 Combination

Replace \* symbol in model number with letter indicating color desired: A=Amber, B=Blue, R=Red, C=White



## OPTIONS

5FLANGEB	Flange	Black
5FLANGEC		Chrome
5FLANGEP	Polished Aluminum Flange	Aluminum
5GROMMET	Rubber Grommet Mount Kit	Black
5GBKT1	"L" Bracket for use with 5GROMMET only	Black
5BKT1	Universal Mount Bracket	Black
5LSMAB	Surface Mount Adapter for Linear Super-LED Only	Black
5LSMAC	Surface Mount Adapter for Linear Super-LED Only	Chrome
5BKT1	Universal Mounting Bracket for 500 Series Super-LED®	Black

**⚠ WARNING:** These products may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit [whelen.com/regulatory](http://whelen.com/regulatory).



# V23™ Series



## FEATURES

- Models have 3-in-1 180° wide-angle warning, illumination, and puddle light
- Includes surface mount Black flange
- Warning segment has 25 Scan-Lock™ flash patterns
- Go undercover with SAE Class 1 Certified Smoked lenses
- Six inch pigtail with sync wire allows up to eight lighthead to be synchronized together for the warning segment of the lighthead
- Amp Draw @ 12 VDC, Warning: 0.76/P, 0.30/A, Flood: 0.62/A, Puddle: 0.12/A
- Size: 2.68" (68mm) H x 1.5" (38mm) D x 4.25" (108mm) L

### Warning Certified To:

- SAE J595
- SAE J845 Selective Coverage



V23RTPB



V23BTPB with V23PEDC

## MODELS

V23*TPB	Combination 180° Warning, Take-Down and Puddle Light Combination	Clear Lens	Black Flange
V23*TPC		Clear Lens	Chrome Flange
V23*TPBX		Smoked Lens	Black Flange
V23*TPCX		Smoked Lens	Chrome Flange

Replace \* symbol in model number with letter indicating color desired: A=Amber, B=Blue, R=Red, C=White



## OPTIONS

V23P20B	20° Angled Surface Mount Housing	Black
V23P20C		Chrome
V23PEDB	Pedestal Mount Kit	Black
V23PEDC		Chrome

**⚠ WARNING:** These products may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit [whelen.com/regulatory](http://whelen.com/regulatory).



## 400 V-Series™

### FEATURES

- Models have 3-in-1 180° wide-angle warning, illumination, and puddle light
- Surface mount, supplied with rubber gasket
- Warning segment has 25 Scan-Lock™ flash patterns
- Six inch pigtail with sync wire allows up to eight lighthoods to be synchronized together for the warning segment of the lighthood
- Amp Draw @ 12 VDC, Warning: 1.2/A, Flood: 0.40/A, Puddle: 0.12/A
- Size: 3" (76mm) H x 1.65" (42mm) D x 4.88" (124mm) L

### Warning Certified To:

- KKK 1822-F Lower
- CAC Title XIII
- NFPA 1901

## M4 V-Series

### FEATURES

- Models have 2-in-1 combination warning and perimeter lighting
- Surface mount
- Warning segment has 25 Scan-Lock flash patterns
- Six inch pigtail with sync wire allows up to eight lighthoods to be synchronized together for warning segment of the lighthood
- Amp Draw @ 12 VDC, Warning: 1.0/P, 0.40/A, Perimeter: 0.77/A
- Size: 3.38" (86mm) H x 1.85" (47mm) D x 5.5" (139mm) L



4V3A

### MODEL

4V3*	Surface
------	---------

Replace \* symbol in model number with LED color desired:  
A=Amber, B=Blue, C=White, R=Red



### OPTIONS

4FLANGEB	Flange Kit	Black
4EFLANGE	Flange Kit	Chrome
4TSMAB	Super-LED® Surface Mount Adapter, Linear-LED® & Super-LED Only	Black
4TSMAC		Chrome
4EGRILB	Grille-Master™ Housing with Swivel Bracket	Black
4EGRILP		Chrome
4BKT1	Universal "L" Mounting Bracket for 400 Series Lighthood, must be used with 4TSMAB or 4TSMAC Flange	Black



M4V2B

### MODEL

M4V2*	Surface	Optional Flange
-------	---------	-----------------

Replace \* symbol in model number with LED color desired:  
A=Amber, B=Blue, C=White, R=Red



### OPTIONS

M4FB	Flange	Black
M4FC	Flange	Chrome
M4FC400	Flange, adapts M Series to 400 Series Style	Chrome
M4BRUSH	Brush Guard	Black
4BKT1	Universal "L" Mounting Bracket for M4	Black

**⚠ WARNING:** These products may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit [whelen.com/regulatory](http://whelen.com/regulatory).



# M6 V-Series™

## FEATURES

- Models have 2-in-1 combination warning and perimeter lighting
- Surface mount
- Warning segment has 21 Scan-Lock™ flash patterns
- Rear lightbar pods house multiple M6 lighthoods for the 2015-2018 Ford Transit Medium or High Roof
- Six inch pigtail with sync wire allows up to eight lighthoods to be synchronized together for warning segment of the lighthood
- Amp Draw @ 12 VDC, Warning: 1.5/P, 0.60/A, Perimeter: 0.77/A
- Size: 4.29" (109mm) H x 2.25" (57mm) D x 6.75" (171mm) L

### Warning Certified To:

- NFPA 1901 when properly configured
- ASTM / KKK 1822-F Upper and Lower
- NFPA 1917 2013 Edition Upper and Lower
  - Table 7.9.13.5 Optical Power Requirements Large Ambulance
  - Table 7.9.14.4 Optical Power Requirements Small Ambulance
- SAE J595
- SAE J845 Selective Coverage
- CAC Title XIII

### Illumination Certified To:

- AMD 024 Perimeter Illumination Spec
  - M6V2 Two lighthoods on each side of the vehicle
- NFPA 13.10.1.2 Ground Lighting
  - M6V2 One lighthood mounted up to 6'



M6V2R

## MODELS

M6V2*	Surface
M6V2*C	Surface, with Clear outer lens

Replace \* symbol in model number with LED color desired:  
A=Amber, B=Blue, C=White, R=Red



## OPTIONS

M6FC	Flange	Chrome
M6FB	Flange	Black
M6P15C	15° Angled Surface Mount Housing	Chrome
M6P15B		Black
M6FC600	Flange, Adapts M6 to 600 Series Mounting	Chrome
M6PTM5F	Front Light Pod for Eight M6 Lighthoods for the 2015-2018 Ford Transit Medium Roof	Black, paintable to match vehicle
M6PT5R	Rear 2 Piece Light Pod for Six lighthoods, 2015-2018 Ford Transit, Medium or High Roof	
M6PTH5	Front Light Pod for Eight M6 Series Lighthoods for the 2015-2018 Ford Transit High Roof	
M6BRUSH	Brush Guard	Black

**⚠ WARNING:** These products may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit [whelen.com/regulatory](http://whelen.com/regulatory).



## M9 V-Series™

### FEATURES

- Models have 2-in-1 combination warning and scene lighting
- Surface mount
- Includes Chrome plated flange
- Adapter flange kit mounts M9 lighthoods to upper sides of the 2015-2018 Transit for 360° of critical coverage
- Warning segment has 21 Scan-Lock™ flash patterns
- Six inch pigtail with sync wire allows up to eight lighthoods to be synchronized together for the warning segment of the lighthouse
- Amp Draw @ 12 VDC, Warning 2.4/P, 0.96/A, Scenelight: 2.4/A
- Size: 6.5" (165mm) H x 2.60" (66mm) D

### Warning Certified To:

- NFPA 1901 when properly configured
- ASTM / KKK 1822-F Upper and Lower
- NFPA 1917 2013 Edition Upper and Lower
  - Table 7.9.13.5 Optical Power Requirements Large Ambulance
  - Table 7.9.14.4 Optical Power Requirements Small Ambulance
- SAE J595
- SAE J845 Selective Coverage
- CAC Title XIII

### Illumination Certified To:

- AMD 024 Perimeter Illumination Spec
  - M9V2 One lighthouse on each side of the vehicle
- NFPA 13.10.1.1 Ground Lighting
  - M9V2 Two lighthoods



M9V2R

### MODELS

M9V2*	Surface
M9V2*C	Surface, with Clear outer lens

Replace \* symbol in model number with letter indicating color desired: A=Amber, B=Blue, R=Red, C=White



### OPTIONS

M9VFC900	Flange, adapts M9V to 900 Series mounting	Chrome
M9BRUSH	Brush Guard	Black

### 2015-2018 Ford Transit Mounting Options

Upper Side Adapter Flange Kit*		
Medium Roof		
M9HTM5FC	Front Driver & Passenger Side	Chrome
M9HTM5RC	Rear Driver & Passenger Side	
High Roof		
M9HTH5FC	Front Driver & Passenger Side	Chrome
M9HTH5RC	Rear Driver & Passenger Side	

\*Two M9 or M9V Series Lighthoods Purchased Separately

**⚠ WARNING:** These products may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit [whelen.com/regulatory](http://whelen.com/regulatory).

**WHELEN®**

51 Winthrop Road  
Chester, Connecticut 06412-0684  
(860) 526-9504 www.whelen.com

Whelen Engineering reserves the right to upgrade and improve products without notice.  
© 2019 Whelen Engineering Company, Inc. Printed in U.S.A.  
NASCAR® is a registered trademark of the National Association for Stock Car Auto Racing, Inc.  
Code No. 12773L - 09/25/2019

**WHELEN®**  
OFFICIAL WARNING LIGHTS



All products proudly designed, manufactured, and assembled in the U.S.A.  
• ISO 9001 Registered QMS