# PLUG N DIKE, DRY GRANULAR APPLICATIONS

#### **MIXING**

Mix approximately 55% - 45% Plug N Dike to water. Put the water into the container first, then add the Plug N Dike in increments. You do not have to measure exactly. Mix until you have a thick, sticky paste. Keep any unused mixed Plug N Dike in an airtight container. Note: Plug N Dike only mixes with water. It does not form a paste when mixed with gasoline or

diesel.

# APPLICATION – PLUG A LEAKING FUEL TANK

No surface preparation is necessary. Take a handful and apply directly into the hole and around the edges of the leak. Press down to get good adhesion. This will immediately stop the leak. The Plug N Dike will hold about three feet of head pressure. Plug N Dike is a temporary patch. On hot days, it may be necessary to add additional Plug N Dike, because it will tend to dry out faster. It will also adhere to a surface below freezing.

For a stronger patch, apply a quick cure epoxy over the Plug N Dike. The surface has to be clean for the epoxy to adhere.

#### APPLICATION - DIKING

To protect drains or catch basins, lay down a piece of plastic (even a large garbage bag works for short term) over the grate. Pour the dry, granular Plug N Dike around the edges of the plastic and spray it with water. This will seal along the edges, even if the pavement is rough around the grate. It can also seal a curb inlet in the same manner.

To dike and contain, if possible, make a dike of dirt and apply a layer of Plug N Dike on the surface. Wet it down to make the seal. Using dirt as the main part of the dike saves on the amount of Plug N Dike needed. It also can be used to dike a low area for containment.

#### CHEMICAL COMPATIBILITY

Plug N Dike works well with gasoline, diesel and most biofuels, as well as water-based chemicals. It is not recommended to sealing off strong acids, bases, oxidizers or reactives. Plug N Dike is non-toxic and non-flammable.

PND Corporation 14320 NE 21<sup>st</sup> St., Ste. 6 Bellevue, WA 98007 Phone: 425 562-7252

e-mail: plugndik@nwlink.com

www.plugndike.com

# MERICAN COLLOID COMPANY

# SAFETY DATA SHEET

#### 1. Identification

**Product identifier VOLCLAY® FOUNDRY 13-T** 

Other means of identification

CAS number 1302-78-9

Smectite \* Bentonite \* Bentonite, Sodian \* Bentonite, Calcian \* Sodium-activated Bentonite \* Synonyms

Montmorillonite

Recommended use Not available.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

# Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name

American Colloid Company, an MTI Company

Address

2870 Forbs Avenue

Hoffman Estates, IL 60192

**United States** 

Telephone

General Information

800 426-5564

Website E-mail

http://www.colloid.com/MCST/ safetydata@mineralstech.com

Emergency phone number

Emergency

1.866.519.4752/1 760 476 3962

**Americas** 

1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

#### 2. Hazard(s) identification

Physical hazards

Not classified.

Health hazards

Carcinogenicity

Category 1A

Category 1

Specific target organ toxicity, repeated

exposure

Environmental hazards

OSHA defined hazards

Not classified. Not classified.

Label elements



Signal word

Hazard statement

May cause cancer. Causes damage to organs through prolonged or repeated exposure.

**Precautionary statement** 

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke

when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If exposed or concerned: Get medical advice/attention.

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Supplemental information

100% of the mixture consists of component(s) of unknown acute dermal toxicity.

# 3. Composition/information on ingredients

#### Substances

SDS US

5711 Version #: 09 Revision date: 02-July-2018 Issue date: 31-March-2014

1/9

Chemical name	Common name and synonyms	CAS number	%
Bentonite	Smectite Bentonite Bentonite, Sodian Bentonite, Calcian Sodium-activated Bentonite Montmorillonite	1302-78-9	100
Constituents			
Chemical name	Common name and synonyms	CAS number	%
QUARTZ (SIO2)		14808-60-7	<= 6
CRISTOBALITE		14464-46-1	<= 2
Designator that a assertis at		and the second s	

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret. Bentonite is a UVCB substance sub-type 4. The purity of the product is 100 % w/w. Bentonite is composed mainly of smectite group minerals but the composition is varied, as expected for a UVCB substance, and other mineral constituents will be present in small and varying amounts. These minor constituents are not relevant for classification and labelling.

Composition comments

Occupational Exposure Limits for constituents are listed in Section 8. The purity of the product is 100% w/w. Impurities are not applicable for a UVCB substance.

# 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist. No specific first aid measures

noted.

Skin contact Get medical attention if irritation develops and persists. No specific first aid measures noted. Wash

skin with soap and water.

Eye contact No specific first aid measures noted. Do not rub eyes. Rinse with water. Get medical attention if

irritation develops and persists. Flush thoroughly with water. If irritation occurs, get medical

Dust in the eyes will cause irritation. Dusts may irritate the respiratory tract, skin and eyes.

assistance

Ingestion No specific first aid measures noted. Rinse mouth thoroughly. Get medical attention if any

Prolonged exposure may cause chronic effects.

discomfort occurs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed General information Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. No hazards which require special first aid measures. Provide general supportive measures and treat symptomatically.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Use any media suitable for the surrounding fires.

Not applicable, non-combustible,

None known. The product itself does not burn.

Material can be slippery when wet.

Use water spray to cool unopened containers. Material can be slippery when wet.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted. This material will not burn.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Material can be slippery when wet. Wear appropriate protective equipment and clothing during clean up. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. No special precautions are necessary beyond normal good hygiene practices. See Section 8 for additional personal protection advice when handling this product.

# Methods and materials for containment and cleaning up

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Collect dust using a vacuum cleaner equipped with HEPA filter. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into closed container.

# **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

#### 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. In case of insufficient ventilation, wear suitable respiratory equipment. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. No special restrictions on storage with other products. Store in a dry area. Store in original tightly closed container. Keep the container dry. Store in a well-ventilated place. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### Occupational exposure limits

Constituents	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	PEL	0.05 mg/m3	Respirable dust.
QUARTZ (SIO2) (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 CI	FR 1910.1000)		
Constituents	Туре	Value	Form
INERT OR NUISANCE DUSTS	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction,
CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limi	t Values		
Constituents	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
JS. NIOSH: Pocket Guide t	o Chemical Hazards	Q.	
Constituents	Туре	Value	Form
CRISTOBALITE (CAS 4464-46-1)	TWA	0.05 mg/m3	Respirable dust.
QUARTZ (SIO2) (CAS 4808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Appropriate engineering controls

If engineering measures are not sufficient to maintain concentrations of dust particulates below the OEL, suitable respiratory protection must be worn. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter. Wear

dust-resistant safety goggles where there is danger of eye contact.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. No protection is ordinarily required under normal

conditions of use.

Other

Use of an impervious apron is recommended. Normal work clothing (long sleeved shirts and long

pants) is recommended.

Respiratory protection

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Chemical respirator with organic vapor cartridge, full facepiece,

dust and mist filter.

Thermal hazards

Not applicable.

General hygiene considerations Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Use good industrial hygiene practices in handling this material.

# 9. Physical and chemical properties

**Appearance** 

Lump, granular or fine powder.

Physical state

Solid.

Form

Powder. Various.

Color

Odor

Various.

\_ .

None.

Odor threshold

Not applicable.

рH

8.5 - 11

Melting point/freezing point

> 842 °F (> 450 °C) / Not applicable.

Initial boiling point and boiling

range

Not applicable.

Flash point

Not applicable.

**Evaporation rate** 

Not available.

Flammability (solid, gas)

This product is not flammable.

#### Upper/lower flammability or explosive limits

Flammability limit - lower

Not applicable.

(%)

Flammability limit - upper

Not applicable.

(%)

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

Not applicable.

Vapor density

Not applicable.

Relative density

2.6 g/cm<sup>3</sup>

Solubility(ies)

Solubility (water)

 $< 0.9 \, \text{mg/l}$ 

Partition coefficient

Not applicable.

(n-octanol/water)
Auto-ignition temperature

Not applicable. Not applicable.

Decomposition temperature

> 932 °F (> 500 °C)

Viscosity

Not applicable.

Viscosity temperature

Not applicable.

Other information

**Bulk density** 

0.9 - 1.4 g/cm<sup>3</sup>

**Explosive limit** 

Not applicable.

**Explosive properties** 

Not explosive. Not explosive

Explosivity

Not applicable.

Flame extension Flammability

Not applicable.

Flammability (flash back)

Not applicable.

Flammability (Heat of

Not applicable.

combustion)

Not applicable.

Flammability (Train fire) Flammability class

Not applicable. Not applicable.

Flash point class

Not flammable

Molecular formula Molecular weight

**UVCB** Substance Not applicable.

Oxidizing properties

Not oxidizing. None.

Percent volatile pH in aqueous solution 0 % 8.5 - 11

Specific gravity

Not applicable.

VOC

CARB 0%

#### 10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Stable at normal conditions.

Possibility of hazardous

reactions

Will not occur.

Conditions to avoid

Moisture. Avoid temperatures exceeding the decomposition temperature. Contact with

incompatible materials.

Incompatible materials

None known.

Hazardous decomposition

products

None.

# 11. Toxicological information

# Information on likely routes of exposure

Inhalation

May cause damage to organs through prolonged or repeated exposure by inhalation. Dust may

irritate respiratory system.

Skin contact

Dust or powder may irritate the skin. Dust in the eyes will cause irritation.

Eye contact Ingestion

Not classified.

Symptoms related to the physical, chemical and toxicological characteristics

Dusts may irritate the respiratory tract, skin and eyes. None known.

Information on toxicological effects

Acute toxicity

Not classified. Not known.

**Product** 

Species

**Test Results** 

VOLCLAY® FOUNDRY 13-T (CAS 1302-78-9)

Acute

Inhalation

Dust

LC50

Rat

Material name: VOLCLAY® FOUNDRY 13-T

> 5.27 mg/l, 4 hr OECD 436

Product	Specie	s	Test Results
Oral			
Dust			
LD50	Rat		> 2000 mg/kg OECD 425
Constituents	Specie	S	Test Results
CRISTOBALITE (CAS 14464-46	-1)		
<u>Acute</u>			
Oral	_		
LD50	Rat		> 22500 mg/kg
Skin corrosion/irritation	Not classi		
Serious eye damage/eye irritation	Mild irritar	nt to eyes (according to the modified Kay & (	Calandra criteria)
Respiratory or skin sensitization	on		
Respiratory sensitization	Not classi	fied.	
Skin sensitization	Not classi	fied.	
Germ cell mutagenicity	Not classif	fied.	
Carcinogenicity	"There is a persons we quarries as the cancer worker proregulatory dust and reavailable for carcinoger	103, SCOEL (the EU Scientific Committee of ain effect in humans of the inhalation of responding in the information to conclude that the relith silicosis (and, apparently, not in employed in the ceramic industry). Therefore, prever itsk" (SCOEL SUM Doc 94-final, June 20 stection against silicosis can be consistently occupational exposure limits. May cause capspirable crystalline silica should be monitor this product. Sepiolite was evaluated by Inicity to humans"). Based on read-across will ogenic. Therefore classification of bentonite	pirable crystalline silica dust is silicosis. ative risk of lung cancer is increased in les without silicosis exposed to silica dust is enting the onset of silicosis will also reduct 03) According to the current state of the arransured by respecting the existing uncer. Occupational exposure to respirable red and controlled. No carcinogenicity data ARC as class 3 ("Cannot be classified as to the sepiolitic bentonite was assessed as
IARC Monographs. Overail			to baramagementy to not warranted.
CRISTOBALITE (CAS 1 QUARTZ (SIO2) (CAS 1	4464-46-1) 4808-60-7)	1 Carcinogenic to hum 1 Carcinogenic to hum	
		es (29 CFR 1910.1001-1052)	
CRISTOBALITE (CAS 1- QUARTZ (SIO2) (CAS 1 US. National Toxicology Pr	4808-60-7)	Cancer Cancer Report on Carcinogens	
CRISTOBALITE (CAS 14		Known To Be Human (	Carcinogen
OUADTT (OIGH) ISSUE		Reasonably Anticipated	d to be a Human Carcinogen.
QUARTZ (SIO2) (CAS 1		Known To Be Human (	Carcinogen.
eproductive toxicity	Not classifi	*	
pecific target organ toxicity - ngle exposure	Not classifi	ed.	
pecific target organ toxicity - peated exposure	Causes da	mage to organs through prolonged or repea	ted exposure.
spiration hazard	Not an aspi	ration hazard.	
hronic effects	Causes dar	mage to organs through prolonged or repea	ted exposure.
2. Ecological information			·
cotoxicity	The produc	t is not classified as environmentally hazard hat large or frequent spills can have a harm	dous. However, this does not exclude the
Product	- ( ) ti	Species	Test Results
Bentonite (CAS 1302-78-9)			
Aquatic			
	EC50	Freshwater algae	> 100 mg/l, 72 hours
Crustacea	EC50	Coon stripe shrimp (Pandalus danae)	24.8 mg/l, 96 hours
		Dephase	= no mgn, oo nours

Daphnia > 100 mg/l, 48 hours

Material name: VOLCLAY® FOUNDRY 13-T

Product		Species	Test Results
		Dungeness or edible crab (Cancer magister)	81.6 mg/l, 96 hours
Fish	LC50	Freshwater fish	16000 mg/l, 96 hours
		Marine water fish	2800 - 3200 mg/l, 24 hours
sistence and degradability	Not releva	ant for inorganic substances	

Persistence and degradability

Not relevant for inorganic substances

Bioaccumulative potential

Will not bio-accumulate.

Mobility in soil

Bentonite is almost insoluble and thus presents a low mobility in most soils.

Mobility in general

The product has poor water-solubility.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and Its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Store containers and offer for recycling of material when in accordance with the local regulations.

#### 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

#### 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

#### SARA 304 Emergency release notification

Not regulated.

# OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

CRISTOBALITE (CAS 14464-46-1) Cancer QUARTZ (SIO2) (CAS 14808-60-7) Cancer CRISTOBALITE (CAS 14464-46-1) lung effects QUARTZ (SIO2) (CAS 14808-60-7) lung effects

CRISTOBALITE (CAS 14464-46-1) immune system effects QUARTZ (SIO2) (CAS 14808-60-7) immune system effects CRISTOBALITE (CAS 14464-46-1) kidney effects

QUARTZ (SIO2) (CAS 14808-60-7) kidney effects

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

#### SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

# Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Total food additive Direct food additive

Administration (FDA)

GRAS food additive

#### **US** state regulations

#### California Proposition 65



WARNING: This product can expose you to QUARTZ (SIO2), which is known to the State of California to cause

cancer. For more information go to www.P65Warnings.ca.gov.

# California Proposition 65 - CRT: Listed date/Carcinogenic substance

QUARTZ (SIO2) (CAS 14808-60-7)

Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3,

CRISTOBALITE (CAS 14464-46-1) QUARTZ (SIO2) (CAS 14808-60-7)

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico		Yes
*A "Voc" indicates that all same	and the second of the second o	163

<sup>&</sup>quot;A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date 31-March-2014 Revision date 02-July-2018 Version #

**Further information** This safety datasheet only contains information relating to safety and does not replace any product

information or product specification.

HMIS® ratings Health: 3\*

Flammability: 0 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 0 Instability: 0

Material name: VOLCLAY® FOUNDRY 13-T

SDS US

List of abbreviations

SWERF = Size-Weighted Relevant Fine Fraction methodology is a scientific method developed to quantify the content of respirable particles within a bulk product. All details about the SWERF method are available at www.crystallicesilica.eu.

UVCB = a substance of Unknown or Variable composition, Complex reaction products or Biological materials

References For a

For any information on literature references or toxicity/ecotoxicity studies, please contact the supplier.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. American Colloid Company, an MTI Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.