



STAR HEADLIGHT & LANTERN CO.

255HTC STROBES WITH LED DIAGNOSTICS



255HTC



255HTCM



255HTCV

Specifications and Features

- High profile
- Patented LED diagnostic indicator is standard
- Photocell for automatic "night" mode switching
- Modular circuit is completely encapsulated for increased shock and weather resistance
- Field selectable flash patterns via internal jumper for double or quad flash (ships in quad flash)
- RFI protection
- Lightweight polycarbonate, universal flange base: three-hole, permanent mount, 1" pipe mount, optional vacuum magnet mount, and standard magnet mount with cig. plug with on/off switch
- Durable polycarbonate, twist on/off lens
- Dimensions: 6 11/16"H x 6 13/32"Dia.
- Voltage: permanent 12-24V DC, magnet 12V DC
- Approvals: Class I (A, B, C) Class II (R), quad flash
- Amp draw: 2 amps @ 12V DC, 1 amp @ 24V DC
- Lens colors:
 - ■ ■ ■ ■
- Approvals: Class I (A, B, C) Class II (R), (quad flash)

Model Numbers/Descriptions:

255HTC	Tall lens
255HTCM	Tall lens, magnet mount
255HTCV	Tall lens, vacuum magnet mount

SF008 Rev C 2-26-2016



Star Headlight & Lantern Co., Inc.
 455 Rochester Street
 Avon, NY 14414
 Phone: 585-226-9500
 Fax: 888-478-2797
 starheadlight.com



PROUDLY MADE IN THE U.S.A.
 An ISO 9001:2008 Certified Company