

## Oil-Only Contractor Grade Sock/Net Boom #WB510SN - 5" x 10', 4 booms/package



Take control of outdoor spill response with Oil-Only Booms.

- Poly-blend filler repels water while only absorbing oil and other hydrocarbons
- Connectors link booms together to create a containment system big enough to handle almost any spill size
- Provides quick, efficient cleanup to help protect the environment from contaminants; suited for short-term use

### WB510SN Specifications

|                             |  |
|-----------------------------|--|
| <b>Dimensions:</b>          | ext. dia. 5" x 10' L                               |
| <b>Shipping Dimensions:</b> | 20" W x 23" L x 20" H                              |
| <b>Sold as:</b>             | 4 booms per package                                |
| <b>Color:</b>               | May vary   |
| <b>Composition:</b>         | Poly Blend Filler/Polyester Netting/Metal Hardware |
| <b>Recycled Content:</b>    | 100% Post-Industrial Recycled Poly Blend Filler    |
| <b>Absorbency:</b>          | Up to 30 gal. per package                          |
| <b>Absorbency per:</b>      | Up to 7.5 gal. per boom                            |
| <b>Weight:</b>              | 22 lbs.  |
| <b># per Pallet:</b>        | 20   |
| <b>Incinerable:</b>         | Yes  |
| <b>Ship Class:</b>          | 175  |

### Metric Equivalent Specifications

|                             |                                |
|-----------------------------|--------------------------------|
| <b>Dimensions:</b>          | ext. dia. 12.7cm x 3m L        |
| <b>Shipping Dimensions:</b> | 50.8cm W x 58.4cm L x 50.8cm H |
| <b>Absorbency:</b>          | Up to 113.6 L per package      |
| <b>Absorbency per:</b>      | Up to 28.4 L per boom          |
| <b>Weight:</b>              | 10 kg                          |

## WB510SN Technical Information

### Warnings & Restrictions:

Color Variance Notice  
Color may vary.

### Regulations and Compliance:

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 122.26 - Facilities must have a detailed plan in place to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

### Technical Documents:

(Available at [spilltech.com](http://spilltech.com))

Product Data Sheet (PDS)

Safety Data Sheet (SDS)



Online:  
[spilltech.com](http://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[sales@spilltech.com](mailto:sales@spilltech.com)