

Oil-Only Fleet Spill Kit #SPKO-FLEET - Absorbs up to 10.7 Gallons



Be prepared for fast response with a SpillTech® Oil-Only Spill Kit!

SPKO-FLEET Specifications

 Dimensions:
 22" W x 20" L x 9" H

 Shipping
 20" W x 22" L x 9" H

Dimensions:

Sold as: 1 per package

Absorbency: Up to 10.7 gal. per package

Weight: 9.57 lbs.
per Pallet: 32
Incinerable: No
Ship Class: 92.5

Includes: 50 - 10" x 14" White Oil-Only

HeavyWeight FineFiber Pads

(WPF1014H)

2 - 3" x 4' White Oil-Only Sorbent

Socks (WSO430)

1 - 1 lb. Plug & Dike Epoxy Putty (A-

PND)

9 - Assorted Wooden Plugs (A-

WOODPLUGS-LG)

2 - 18" X 30" Yellow Disposal Bag &

Tie (A-DISPBAG-SM)

2 - Pair Nitrile Gloves (A-GLV-NIT)

1 - Safety Goggles (A-GOG)

1 - 8" x 17" x 20" Yellow Nylon "Spill Responder" Zippered Tote Bag (A-

YTOTE)

Metric Equivalent Specifications

Dimensions: 55.9cm W x 50.8cm L x 22.9cm H **Shipping** 50.8cm W x 55.9cm L x 22.9cm H

Dimensions:

Absorbency: Up to 40.5 L per package

Weight: 4.3 kg



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other)

Email: sales@spilltech.com

SPKO-FLEET Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)

