

Tire Size	Gallons	Tire Size	Gallons
ALL 20"	2	All 39"	6
Other 21"	2	All 46"	6
27.25R21	3	Other 49"	5
ALL 24"	2	31/90R49*	6
14.00 - 25	2	24.00 - 51	5
18.00 - 25	2	27.00 - 51	6
385/95R25	2	30.00R51	8
Other 25"	3	33.00R51	8
18.00 - 26	2	36.00R51	8
Other 26"	3	37.5R51	8
28LR - 26*	4	50/65R51	10
750/55R26.5	4	55/65 - 51	10
750/45R26.5	4	60/65 - 51	10
16.9 - 28	3	39/90R53	8
Other 29"	4	All 56.5"	8
775/65R29*	6	37.00R57	10
875/65R29*	6	40.00 - 57	10
67x34 - 30	5	42/90/57	15
30 - 33	4	44.00/57	15
30/65 - 33	4	44/80/R57	15
33.5R33	5	55.5/80 - 57	20
35/65R33	5	60/80R57	20
37.5R33	5	65/65 - 57	20
ALL 34"	4	70/70 - 57	20
ALL 35"	5	All 59.5"	10
ALL 38"	5	All 63"	25

- Use on trucks, busses, construction and off-road applications
- Low speed 80 MPH / 129 KPH
- Operates between -10°F to 230°F (-23°C to 110°C)
- Dissipates tire chamber heat so that tires run cooler, reduces heat build up
- Will not damage TPMS
- Helps retain casing integrity
- Protects the casing from heat, oxidation and UV damage
- Prevents cracks and blisters on inner liners
- Protects wheels/rims against rust scale
- Excellent leak detector that safely identifies cracks in the rim base
- Washes out easily
- Non-toxic, biodegradable, and non-hazardous
- Non-Flammable. Does not support combustion and will not cause a fire in the retread chamber
- DOES NOT void tire manufacturer's warranty
- Manufactured in Canada

www.**KENTOOL**.com
1-888-536-8665



ARDL Tested and Accredited

