

# Ken-Tool ELITE TIRE SEALANT

WHEREVER TIRES ARE CHANGED™

www.KENTOOL.com 1-888-536-8665

768 E. North Street, P.O. Box 9320 | Akron, Ohio 44305 | Fax: 800-872-4929  
E-mail: sales@kentool.com | © 2021 Ken-Tool. All Rights Reserved. KT011421

LAWN-GOLF-ATV		OTR-INDUSTRIAL- MINING- CONSTRUCTION- AGRICULTURE				TOW TRAILERS		TRUCKS-SEMI-COACH-BUS					
Tire Size	Ounces	Tire Size	Ounces	Tire Size	Ounces	Tire Size	Ounces	Tire Size	Ounces	Tire Size	Ounces		
11 x 4.00-5	11	8.25R15	77	480/65-R24	240	18.4-38	280	4.8-8	15	205/80 R16	30	255/70R22.5	50
11 x 6.00-5	13	10.00R15	86	26.5R25	317	20.8-38	400	18.5 x 8.50-8	21	8R17.5	34	265/75R22.5	56
13 x 5.00-6	14	14.0/65-15	98	29.5R25	350	520/85-38	370	6.90-9	19	9R17.5	38	275/70R22.5	56
15 x 6.00-6	18	14.5R15	119	30/65R25	299	710/70R38	642	6.50-10	21	215/75R17.5	34	275/80R22.5	58
4.80/4.00-8	18	17.4-15	137	445/95R25	215	16.9-46	260	205/50-10	20	245/80R17.5	38	295/75R22.5	59
5.70-8	21	300/65R15	90	685/80R25	296	18.4-46	320	4.80-12	15	7.50R18	36	295/80R22.5	61
16 x 6.50-8	21	400/80R15	101	750/65R25	290	21.00R49	482	23.5 x 8.50-12	25	8R19.5	34	305/70R22.5	58
18 x 8.50-8	30	95/65-15	86	16.00-26	206	24.00R49	548	6.00-13	20	15R19.5	68	305/85R22.5	62
25 x 12.00-9	62	7.50-16	74	18.00-26	230	27.00R49	614	7.75-14	20	225/70R19.5	38	315/80R22.5	67
18 x 8.50-10	32	11.00R16	98	23.1-26	310	31/90R49	749	8.00-14.5	25	225/75R19.5	40	385/65R22.5	72
18 x 11.00-10	40	12.00-16	105	28LR-26	360	24.00-51	569	7.00-15	25	245/70R19.5	43	425/65R22.5	94
22 x 9.50-10	42	12.5/70-16	110	750/55R26.5	320	33.00R51	776	12.00-15	25	285/70R19.5	49	445/50R22.5	120
22 x 11.00-10	48	16.00R16	134	16.9-28	233	50/65R51	965	6.00-16	25	305/70R19.5	54	445/65R22.5	105
24 x 12.00-10	55	10-16.5	95	20/65-29	236	60/65-51	1,151	8.00-16	25	445/65R19.5	72	455/50R22.5	120
21 x 8.50-12	36	12.5/65-18	104	26.5R29	365	39/90R53	902	8.25-16	30	10.00R20	50	455/55R22.5	112
22 x 9.50-12	41	15.5/70-18	125	29.5R29	404	27.00-56.5	714	11.00-16	30	365/80R20	76	495/45-22.5	115
23 x 8.50-12	45	13.5-20	140	775/65R29	510	30.00-56.5	779	8.00-16.5	30	395/85R20	81	12.00R24	72
23 x 10.50-12	57	14.00R20	146	16.9-30	248	37.00R57	965	12.00-16.5	40	14.00R21	76	14.00R24	86
26 x 12.00-12	66	16.00-20	164	30.5-32	480	42/90/57	1,266	7.00-17.5	35	16.00R21	86	11R24.5	61
24 x 8.50-12	43	17.5/65-20	149	35.5-32	704	44/80/R57	1,137	14R17.5	46	24R21	125	12R24.5	68
25 x 11.00-12	50	335/80R20	130	27.00R33	419	60/80R57	1,700	7.50R18	29	10.00R22	58	13.5R24.5	76
26.5 x 14.00-12	54	425/95R20	170	33.5R33	515	70/70 - 57	1,960	8R19.5	27	10R22.5	54	245/75R24.5	56
27 x 10.50-15	64	42 x 17-20	210	37.5R33	575	33 - 59.5	870	225/70R19.5	30	11R22.5	58	275/80R24.5	61
29 x 12.50-15	78	12.00R21	134	540/65-R34	360	39 - 59.5	1,061	285/70R19.5	39	12R22.5	61	285/75R24.5	61
31 x 13.50-15	84	14.00R21	152	21.00R35	350	53/80 - 63	1,730	445/45R19.5	54	235/80R22.5	49	12.00-25	77
31 x 15.50-15	96	16.00R21	170	24.00R35	398	59/80 - 63	1,800	445/65R19.5	58	245/70R22.5	50	14.00-25	88

Tires not found? Use the formula below to calculate the amount of Ken-Tool Elite Sealant ounces required per tire.  
OTR-Diameter (Inches) X Width (Inches) Divided by 4 = Ounces / Tow Trailers D x W Div 12 = Ounces / Trucks-  
Semi-Coach-Bus D x W Div 8 = Ounces  
Example for 25 x 8 x 12 ATV tire: Overall diameter (in) 25" X Overall width (in) 8" = 200 divided by 4 = 50 FL. OZ

\*Add 25% more product to Bias-ply tires and Tube type tires.

\*Tube type tires to be in motion for Ken-Tool Elite Sealant to fully stop air porosity.  
Manufactured in Canada.