



OTR ELITE TIRE SEALANT

www.KENTOOL.com 1-888-536-8665

768 E. North Street, P.O. Box 9320 | Akron, Ohio 44305 | Fax: 800-872-4929
E-mail: sales@kentool.com | © 2021 Ken-Tool. All Rights Reserved. KT011421

Tire Size	Ounces	Tire Size	Ounces	Tire Size	Ounces	Tire Size	Ounces	Tire Size	Ounces	Tire Size	Ounces	Tire Size	Ounces
10 x 4.50-5	9	23x10.00-10	46	8.5/90-15	74	335/80R20	130	26.5R25	317	30/65-33	386	27.00-51	614
11 x 3.60-5	10	24x9.50-10	48	9.00R15	80	425/95R20	170	29.5R25	350	33.5R33	515	30.00R51	707
11 x 4.00-5	11	24x12.00-10	55	10.00R15	86	42x17-20	210	30/65R25	299	35/65R33	446	33.00R51	776
11 x 4.50-5	12	21x8.50-12	36	14.0/65-15	98	12.00R21	134	385/95R25	194	37.5R33	575	36.00R51	842
11 x 6.00-5	13	22x7.50-12	39	14.5R15	119	14.00R21	152	445/80R25	200	480/85-R34	290	37.5R51	878
13 x 5.00-6	14	22x9.50-12	41	17.4-15	137	16.00R21	170	445/95R25	215	540/65-R34	360	50/65R51	965
13 x 6.50-6	15	23x8.50-12	45	300/65R15	90	24R21	245	685/80R25	296	21.00R35	350	55/65-51	1,058
14 x 4.50-6	16	23x9.50-12	51	350/65R15	98	24-21	245	750/65R25	290	24.00R35	398	60/65-51	1,151
15 x 5.00-6	17	23x10.50-12	57	400/80R15	101	27.25R21	278	16.00-26	206	29.5R35	482	39/90R53	902
15 x 6.00-6	18	24x9.50-12	45	95/65-15	86	27.25R21	278	18.00-26	230	33.25R35	542	27.00-56.5	714
4.80/4.00-8	18	24x12.00-12	58	7.50-16	74	10-22.5	122	23.1-26	310	15.5-38	220	30.00-56.5	779
5.70-8	21	24x13.00-12	62	9.00R16	86	11-22.5	131	28LR-26	360	18.4-38	280	37.00R57	965
15 x 6.50-8	21	26x12.00-12	66	10.5/80-16	90	13-22.5	152	750/55R26.5	320	20.8-38	400	40.00-57	1,220
16 x 6.50-8	21	24x8.50-12	43	11.00R16	98	16.5-22.5	188	750/45R26.5	320	520/85-38	370	42/90/57	1,266
16 x 7.50-8	27	25x10.50-12	74	12.00-16	105	17.5-22.5	200	16.9-28	233	710/70R38	642	44.00/57	1,322
18 x 6.50-8	24	25x11.00-12	50	12.5/70-16	110	10.00-24	128	20/65-29	236	45/65R39	685	44/80/R57	1,137
18 x 7.50-8	27	26.5x14.00-12	54	16.00R16	134	12.00R24	149	26.5R29	365	18.4-42	300	55.5/80 - 57	1,620
18 x 8.50-8	30	27x8.50-15	60	10-16.5	95	13.00R24	161	29.5R29	404	55/65R45	935	60/80R57	1,700
25 x 12.00-9	62	27x10.50-15	64	12.5/65-18	104	14.00R24	170	30/65R29	341	16.9-46	260	65/65 - 57	1,860
5.00-10	22	29x12.50-15	78	15.5/60-18	119	16.00R24	191	775/65R29	510	18.4-46	320	70/70 - 57	1,960
18 x 8.50-10	32	29x14.00-15	84	15.5/70-18	125	16.9-24	203	875/65R29	520	18.00R49	416	33 - 59.5	870
18 x 10.50-10	38	31x12.00-15	78	13.5-20	140	18.4-24	218	16.9-30	248	21.00R49	482	36 - 59.5	980
18 x 11.00-10	40	31x13.50-15	84	14.00R20	146	19.5-24	230	30.5-32	480	24.00R49	548	39 - 59.5	1,061
19.5 x 8.25-10	30	31x15.50-15	96	14/70-20	130	21.00-24	245	35.5-32	704	27.00R49	614	53/80 - 63	1,730
22 x 9.50-10	42	200-50	66	16.00-20	164	385/95R24	173	27.00R33	419	31/90R49	749	55/80 - 63	1,740
22 x 11.00-10	48	8.25R15	77	17.5/65-20	149	480/65-R24	240	30-33	464	24.00-51	569	59/80 - 63	1,800

Tires not found? Use the formula below to calculate the amount of Ken-Tool OTR Sealant ounces required per tire.
ATV, Industrial, Agriculture, OTR tires - Diameter (Inches) X Width (Inches) Divided by 4 = Ounces
Example for 25 x 8 x 12 ATV tire: Overall Diameter (in) 25" X Overall Width (in) 8" = 200 divided by 4 = 50 FL. OZ

*Add 25% more product to Bias-ply tires and Tube type tires.
*Tube type tires to be in motion for Ken-Tool OTR Sealant to fully stop air porosity.
Manufactured in Canada.