



# Pertinent Dimensions for End Fittings and Links

## Wire Rope Slings

## Specifications



ROPE DIA INCHES	1 LOOP		2 THIMBLE		3 ALLOY HOOK *w/ THIMBLE	4 SHACKLE with THIMBLE	5 HALF THIMBLE		6 OPEN SWAGED SOCKET		7 CLOSED SWAGED SOCKET		8 OPEN SPELTER SOCKET		9 CLOSED SPELTER SOCKET	
	INSIDE		INSIDE		Size (TONS)	Size (IN)	INSIDE		Pin Dia (IN)	Jaw Opening (IN)	Hole Dia (IN)	Head Thick- ness (IN)	Pin Dia (IN)	Jaw Open- ing (IN)	Hole Dia (IN)	Head Thick- ness (IN)
	Width (IN)	L (IN)	Width (IN)	L (IN)			Width (IN)	L (IN)								
	6 x 19 WITH I.W.R.C.															
1/4	2	4	7/8	1 5/8	1	5/16	----	----	11/16	11/16	3/4	1/2	11/16	11/16	.88	.50
5/16	2 1/2	5	1 1/16	1 7/8	1 1/2	3/8	----	----	13/16	13/16	7/8	11/16	13/16	13/16	.97	.69
3/8	3	6	1 1/8	2 1/8	2	7/16	2	4	13/16	13/16	7/8	11/16	13/16	13/16	.97	.69
7/16	3 1/2	7	1 1/4	2 3/8	3	1/2	2 1/4	5	1	1	1 1/16	7/8	1	1	1.16	.88
1/2	4	8	1 1/2	2 3/4	3	1/2	2 1/4	5 1/2	1	1	1 1/16	7/8	1	1	1.16	.88
9/16	5	10	1 3/4	3 1/4	5	5/8	3 1/4	7	13/16	1 1/4	1 1/4	1 1/8	1 3/16	1 1/4	4.41	1.00
5/8	5	10	1 3/4	3 1/4	5	5/8	3 1/4	7	13/16	1 1/4	1 1/4	1 1/8	1 3/16	1 1/4	1.41	1.00
3/4	6	12	2	3 3/4	7	3/4	3 1/4	9	1 3/8	1 1/2	1 15/32	1 5/16	1 3/8	1 1/2	1.66	1.25
7/8	7	14	2 1/4	4 1/4	11	7/8	4 1/2	10 1/2	1 5/8	1 3/4	1 23/32	1 1/2	1 5/8	1 3/4	1.94	1.50
1	8	16	2 1/2	4 1/2	11	1	4 1/2	12	2	2	2 3/32	1 3/4	2	2	2.30	1.75
1 1/8	9	18	2 7/8	5 1/8	15	1 1/8	4 5/8	13 1/2	2 1/4	2 1/4	2 11/32	2	2 1/4	2 1/4	2.56	2.00
6 x 37 WITH I.W.R.C.																
1 1/4	11	22	2 7/8	5 1/8	22	1 1/4	5 1/2	15	2 1/2	2 1/2	2 19/32	2 1/4	2 1/2	2 1/2	2.81	2.25
1 3/8	12	24	3 1/2	6 1/4	22	1 3/8	6	17	2 1/2	2 1/2	2 19/32	2 1/4	2 1/2	2 1/2	2.81	2.25
1 1/2	13	26	3 1/2	6 1/4	30	1 1/2	6 1/2	18	2 3/4	3	2 7/8	2 1/2	2 3/4	3	3.19	2.50
1 3/4	15	30	4 1/2	9	37	1 3/4	7	21 1/2	3 1/2	3 1/2	3 5/8	3	3 1/2	3 1/2	3.75	3.00
2	16	32	6	12	37	2	7	26	3 3/4	4	3 13/16	3 1/4	3 3/4	4	4.38	3.25
2 1/4	18	36	7	14	45	2 1/2	----	----	----	----	----	----	4 1/4	4 1/2	5.00	3.63
2 1/2	20	40	----	----	60	2 1/2	----	----	----	----	----	----	4 3/4	5	5.50	4.00

\*Alloy Hooks are supplied with safety latches.